



IN STAT+ 2R



IN STAT+ 3R




IN STAT+ 3F


Varianten | Variations

| Bestellbez. Type | INSTAT+ 2R | INSTAT+ 3R | INSTAT+ 3F** |
|---------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Artikel-Nr. Article No. | 0537 10 291 900 | 0537 20 141 900 | 0537 30 141 900 |
| Raumregler Room temperature controller Temp. 7...32°C | ● | ● | |
| Fußbodenregler Underfloor heating controller Temp. 10...40°C | | | ● |
| Betriebsspannung Supply voltage | Batterie: 2 x 1,5V (AA), Lebensdauer ≥ 3 Jahre Battery: 2 x 1,5V (AA), Service life ≥ 3 years | Netz; AC 230V, 50 Hz mains; AC 230V, 50 Hz | Netz; AC 230V, 50 Hz mains; AC 230V, 50 Hz |
| Fernfühler Remote sensor | – | – | im Lieferumfang enthalten F 193 720, Länge 4 m, verlängerbar auf 50 m included in delivery F 193 720, length 4 m, extendable up to 50 m |
| Fühlerüberwachung Sensor monitoring | – | – | 30% Heizen bei Fühlerfehler 30% heating when sensor error |

Schaltzeichnung | Wiring diagram



INSTAT+ 2R



INSTAT+ 3R, 3F

